

TIERRA

NOBLE & NATURAL

Mar **8"** **Character**
Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔL_w : 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



TIERRA

NOBLE & NATURAL

Cielo **8"** **Character**
Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



TIERRA

NOBLE & NATURAL

Sol **8"** **Character**
Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔL_w : 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



TIERRA

NOBLE & NATURAL

Arena **8"** **Character**
Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔL_w : 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



TIERRA

NOBLE & NATURAL

Monte
Name

8"
Width

Character
Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔL_w : 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

